US 20140013643A1

(19) United States

(12) Patent Application Publication

(10) Pub. No.: US 2014/0013643 A1

(43) Pub. Date: Jan. 16, 2014

Davis et al.

(54) ACCESSORY INTERFACE SYSTEM

(71) Applicants: **Jason M. Davis**, Loogootee, IN (US); **Brian P. Dean**, Bloomington, IN (US); **Brandon R. Clarke**, Bloomington, IN (US)

(72) Inventors: **Jason M. Davis**, Loogootee, IN (US); **Brian P. Dean**, Bloomington, IN (US); **Brandon R. Clarke**, Bloomington, IN (US)

(21) Appl. No.: **13/865,292**

(22) Filed: **Apr. 18, 2013**

Related U.S. Application Data

(62) Division of application No. 13/168,459, filed on Jun. 24, 2011, now Pat. No. 8,479,434.

Publication Classification

(51) **Int. Cl.**
F41A 23/02 (2006.01)

(52) **U.S. Cl.**
CPC *F41A 23/02* (2013.01)
USPC **42/90**

(57) **ABSTRACT**

An apparatus for mounting accessories on a weapon mount. One embodiment of the apparatus includes an accessory interface system having a forward module coupled to a mounting module. The mounting module of the accessory interface system mounts on a weapon mount. The forward module of the accessory interface system provides a plurality of surfaces for mounting weapon accessories.

(b)



FIG 1


160
163
162
161
162
114
109
113
103
107
112
107
109
101
107
100
105
106
102
106
108
104
104
104
106
104
106
104
106

FIG 2(a)


101
200
210
220
212
222
214
224
216
226
218
202
202
204

FIG 2(b)


101
210
218
220
226
212
216
214
222
224

FIG 2(c)


109
262
262
262
252
252
252
252
252
252
252
252
252
252
252
256
256
256
202
246
204
101
241
242
231
230
240
218
226
216
224
104
104

FIG 2(d)


204
241
231
230
240
232
101
218
216
214
226
224
222
242
243

FIG 3(a)



FIG 3(b)



FIG 3(c)



FIG 3(d)



FIG 4(a)



FIG 4(b)



FIG 4(c)



FIG 4(d)



FIG 4(e)


571
580
575
570
580
580
550
578

FIG 4(f)


571
571
570
103
570
575
575
573
573
550
114
114

FIG 5(a)



FIG 5(b)



FIG 6(a)



FIG 6(b)



FIG 7


114
613
103
113
115
580
112
109
262
262
262
611
611
101
105
102
352
621
621
621
352
619
107
106
623
623
623
623
623
623
623
623
611
611
611

FIG 8(a)





FIG 8(b)

FIG 8(c)



FIG 9



ACCESSORY INTERFACE SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority to U.S. patent application Ser. No. 13/168,459, filed Jun. 24, 2011, entitled "ACCESSORY INTERFACE SYSTEM," the disclosure of which is expressly incorporated by reference herein.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

[0002] The invention described herein includes contributions by one or more employees of the Department of the Navy made in performance of official duties and may be manufactured, used and licensed by or for the United States Government for any governmental purpose without payment of any royalties thereon.

BACKGROUND OF THE INVENTION

[0003] In the status quo, heavier weapons or equipment items, e.g., heavy machine guns, are mounted on stands, including portable stands, to assist with the stability and ease of using such items. Stands may be used in a wide variety of end uses including on moving platforms, portable applications, fixed sites, submersible vehicles, moving vehicles, airborne applications, to name a few. Users of these mounted guns also desire the use of accessories with the weapons. For example, a user desires using targeting aids, such as a light, laser, or sight, to help increase the effectiveness of using the equipment item or weapon. Additionally, the user may desire increased protection or armament while using the weapon. For example, a user desires using a ballistic shield. An accessory might be attached directly to an equipment item or weapon or might be attached to a rail system that is connected to the weapon. For example, a laser sighting device is attached to a weapon near the rear of the weapon and a ballistic shield is attached to the weapon in between the laser sighting device and the front of the weapon. The ballistic shield is also in between the front of the weapon and the user of the weapon. A disadvantage to this approach is the possibility of obstruction by the shield, resulting in "splash-back" of laser radiation. Such splash-back may "bloom-out" a weapon user's night vision, effectively blinding the user. It can also be an eye safety concern, depending on the location of personnel in relation to any reflected laser radiation. Another difficulty with attempts to create accessory mounting systems is creating a mounting system which is compatible with more than one shield or shroud design which also meets other needs and satisfies design, manufacturing constraints, a wide variety of real world field events and failure modes, mounting scenarios, equipment/weapon types, equipment interaction limitations, or environmental constraints, such as described in this application.

[0004] In the case of some other weapons, especially heavy equipment or weapon systems, rail systems might mount directly to the weapon or to the shroud of the weapon. Such direct or shroud mounted systems place undesired stresses on the weapon itself. Furthermore, weapon shrouds are also typically non-uniform in positioning, often resulting in the rail system, and hence the accessories, being in an undesired and often non-uniform, unusable, and unreliable orientation which creates unpredictable, damaging, or undesired effects in field use. Thus, it would be desirable to have an accessory mounting system that does not mount on the weapon or the shroud of the weapon. Furthermore, it would be desirable to have an accessory mounting system that is uniformly positioned and modular. Additional features such as minimized weight and strength are also desired by users in combination with the various desired features.

[0005] Accessory mounting systems have limited capabilities and can be overloaded by the weight and orientation of the accessories connected to its components, e.g., a rail system. An overloaded rail can impact the area connected to the rail system. For example, an overloaded rail system on a weapon or weapon shroud can warp the weapon or the weapon shroud, thereby damaging the weapon or weapon shroud and affecting the performance of the weapon. Therefore, it would be desirable to have a rail system that addresses overloading of the rail system.

[0006] With increased use of accessories on a rail system, also comes the increased management of collateral items that accompany the accessories. For example, many accessories have collateral items, e.g., cables, (e.g., electrical, power, control, and other wise) coupled to the accessory that must be located somewhere. The cable can dangle from the weapon, which could significantly affect the user of the weapon and his use of the weapon, or, preferably, it can be managed on the weapon. Therefore, it would be desirable to have an accessory mounting system that also addresses management of collateral items.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. **1** depicts an accessory interface system in accordance with an exemplary embodiment;

[0008] FIGS. **2**(*a*)-**2**(*d*) depict the forward module of FIG. **1** in greater detail;

[0009] FIGS. **3**(*a*)-**3**(*d*) depict the ancillary rail module of FIG. **1** in greater detail;

[0010] FIGS. **4**(*a*)-**4**(*f*) depict the mounting module of FIG. **1** in greater detail;

[0011] FIGS. **5**(*a*) and **5**(*b*) depict the rail system of FIG. **1** in greater detail;

[0012] FIGS. **6**(*a*) and **6**(*b*) depict a second rail system of FIG. **1** in greater detail;

[0013] FIG. **7** depicts the assembly of components parts of the accessory interface system;

[0014] FIGS. **8**(*a*)-(*c*) depict the accessory interface system in application with a weapon and weapon mount; and

[0015] FIG. **9** depicts the accessory interface system in application with a weapon, weapon mount, and ballistic shield.

DETAILED DESCRIPTION OF THE INVENTION

[0016] In the following detailed description, reference is made to the accompanying drawings, which form a part hereof, and in which is shown by way of illustration specific exemplary embodiments of the invention. These embodiments are described in sufficient detail to enable those of ordinary skill in the art to make and use the invention, and it is to be understood that structural, logical, or other changes may be made to the specific embodiments disclosed without departing from the spirit and scope of the present invention.

[0017] The invention discloses an accessory interface system that enables the mounting of weapon accessories to a weapon mount. The invention also discloses an accessory interface system that enables uniform positioning of acces-

sories and modularity. The invention also discloses an accessory interface system that addresses overloading of the rail system. The invention also discloses an accessory interface system that addresses management of collateral items.

[0018] An accessory interface system **100** is depicted in FIG. **1** in accordance with an exemplary embodiment of the invention. An accessory interface system **100** includes a forward module **101**, an ancillary rail module **102**, and a mounting module **103**. The exemplary accessory interface system **100** employs a dual load bearing or traverse portions **202** (FIG. **2**(*a*)) or beam design which is coupled into a buffer system **163** of a weapon mount **160**, using a fastening system **115** coupled to a fastening system of the weapon mount. In this embodiment, a weapon mount cross member **161** is part of the buffer system **163**. However, another embodiment of an alternative embodiment for the invention can include substitution of a dual load bearing or beam structure that can incorporate a single load bearing structure or more than two load bearing structures provided the below and above referenced design parameters, including problems associated with elevation or freedom of movement of a mounted equipment item, are adequately addressed and evaluated in required testing. The fastening system **115** includes, for example, bolts **112** and washers **113** employed through apertures **114** of the accessory interface system **100**. The bolts **112** are received and coupled to the fastening system of the weapon mount, for example, the bolts **112** are received through apertures **162** and coupled to respective nuts or threaded sections (for simplicity, not shown) in the interior of a buffer system **163**.

[0019] The underside of the forward module **101** is open for the majority of its length, to reduce the likelihood of obstructing a vertical path of a weapon that is mounted in the weapon mount **160**, thus increasing the likelihood of enabling the weapon to achieve full depression. Five mounting surfaces **104** for accessories are provided at the free end, e.g., the front end or end away from the weapon mount **160**, of the load bearing or traverse portions of the accessory interface system **100**. Each mounting surface **104** includes, for example, a rail system **106**, is equidistant from a common centerline located within the accessory interface system **100**. In a preferred approach, the common centerline is substantially the same as a centerline of a weapon mounted in the weapon mount **160** and accessory interface system **100**, e.g., where the centerline is also the centerline of the interior of the barrel of the weapon. Along its length, the accessory interface system **100** contains collateral clamps **107**, e.g., cable clamps, allowing management of accessory collaterals, e.g., cables. For example, the accessory collaterals are routed from an accessory mounted on a rail system **106** back to the rear of weapon system for remote operation.

[0020] In a preferred approach, an accessory interface system **100** also comprises an upward arching ancillary rail module **102**, which is mounted on forward module **101** above a weapon. The ancillary rail module **102** has, on its top side, a mounting surface **108** for accessories. The mounting surface **108** includes, for example, a rail system **105**, which is equidistant from the common centerline located within the accessory interface system **100**, being the same common centerline that the mounting surface **104** is equidistant from. The ancillary rail module **102** can be mounted at different locations along the top of the forward module **101**. Further descriptions of the accessory interface system **100** are provided below.

[0021] FIGS. **2**(*a*)-**2**(*d*) depict the forward module **101** in greater detail. FIG. **2**(*a*) depicts a top view of an initial stage of formation of a forward module **101** of FIG. **1**. In an exemplary embodiment, forward module **101** is formed from a "U" shaped, substantially flat metal blank **200**, where the metal is quarter inch (0.25") metal. Metal blank **200** has an interface portion **204** and two load bearing or traverse portions **202**. The interface portion **204** is substantially rectangularly shaped having an approximate height being six and three quarter inches (6¾") and a width of approximately eight inches (8"). Each load bearing or traverse portion **202** is approximately one and one half inches (1½") in height and thirteen inches (13") in width. A top edge of one of the load bearing or traverse portions **202** is shared by a top edge of interface portion **204**. A bottom edge of other of the load bearing or traverse portions **202** is shared by the bottom edge of interface portion **204**.

[0022] The interface portion **204** is subdivided into further substantially rectangular portions: first portion **210**, second portion **212**, third portion **214**, fourth portion **216** and fifth portion **218** as depicted in FIG. **2**(*a*). First portion **210** and fifth portion **218** are approximately one and one half inches (1½") in height. Second portion **212**, third portion **214**, and fourth portion **216** are approximately one and one quarter inches (1¼") in height. The interface portion **204** also includes bend regions: first bend region **220**, second bend region **222**, third bend region **224**, and fourth bend region **226**. The bend regions represent where the metal blank **200** is bent during formation to form the desired shape of the forward module **101**.

[0023] Metal blank **200** is bent along first bend region **220** to form a forty five (45) degree between a plane formed by the face of first portion **210** and a plane formed by the face of second portion **212**. Metal blank **200** is further bent along second bend region **222** to form a forty five (45) degree between a plane formed by the face of second portion **212** and a plane formed by the face of third portion **214**. Metal blank **200** is further bent along third bend region **224** to form a forty five (45) degree between a plane formed by the face of third portion **214** and a plane formed by the face of fourth portion **216**. Metal blank **200** is further bent along fourth bend region **226** to form a forty five (45) degree between a plane formed by the face of fourth portion **216** and a plane formed by the face of fifth portion **218**.

[0024] FIG. **2**(*b*) depicts a front perspective view of forming an intermediate stage of forward module **101** of FIG. **1**. FIG. **2**(*b*) shows the interface portion **204** after being bent. As a result of the bending, first portion **210** is at a 45 degree angle with respect to second portion **212**. Second portion **212** is at a 45 degree angle with respect to third portion **214**. Third portion **214** is at a 45 degree angle with respect to fourth portion **216**. Fourth portion **216** is at a 45 degree angle with respect to fifth portion **218**.

[0025] FIG. **2**(*c*) depicts a side perspective view of forming a later stage of forward module **101** of FIG. **1**. FIG. **2**(*c*) shows the interface portion **204** and the load bearing or traverse portions **202** after apertures are included. Although only one side of forward module **101** is depicted, the one side is representative of apertures applied to the other side, such that both sides are substantially symmetric.

[0026] A plurality of apertures is applied to mounting surfaces **104** (FIG. **1**) to permit mounting of a rail system **106** (FIG. **1**) on each of the mounting surfaces, respectively. Thus, first portion **210**, second portion **212**, third portion **214**, fourth

portion **216**, and fifth portion **218** include a plurality of apertures to couple a rail system **106** to the respective portion. Thus, fifth portion **218** includes a plurality of, e.g., four (4) apertures **230**; fourth portion **216** includes a plurality of, e.g., four (4) apertures **231**. Although not depicted in FIG. **2**(*c*), third portion **214**, second portion **212** and first portion **210** include a plurality of, e.g., four (4) apertures. The size, number, and orientation of apertures depend on the rail system to be coupled to so that the apertures in the mounting surface correspond to apertures in the rail system so that the rail system **106** can be coupled to the mounting surface **104**. The apertures, e.g., apertures **230**, in the portions, e.g., fifth portion **218**, are substantially equally spaced and co linear such that a rail system is capable of being fastened to all the portions. For example, a rail system is fastened to fifth portion **218** using apertures **230**. The same rail system is fastened, at a different time, to fourth portion **216** using apertures **231**. The same rail system can also be fastened at different times, to third portion **214**, second portion **212** and first portion **210** using the respective apertures in the portions. Each rail system **106** is substantially the same height so that the top surface of each rail system mounted on a mounting surface is substantially equidistant from a common center line of the weapon (i.e., the heights of the rail systems are substantially the same). Preferably, each rail system **106** is mounted such that an imaginary line passing through the center line of the rail system **106** is co-planer to the centerline of the weapon. Thus, an equipment item mounted on a first rail system **106** is same distance to the center line of the weapon as when the equipment item is mounted on a second rail system **106**. Additionally, the alignment of the equipment item mounted on a first rail system **106** is same alignment to the center line of the weapon as when the equipment item is mounted on a second rail system **106**. Thus, ideally, once an equipment item has a preferred alignment on a first rail system **106** with respect to the center line of the weapon, when the equipment item is relocated to a second rail system **106**, the equipment item should not require any additional adjustment to have the same alignment to the center line of the weapon as when the equipment item was on the first rail system.

[0027] Portion **218**, and similarly portion **210** (not shown) include a plurality of weight reduction apertures **240** which are used to remove some of the weight of the forward module **101** without impacting the effectiveness of forward module **101**. Fourth bend region **226** and third bend region **224**, and similarly second bend region **222** (not shown) and first bend region **220** (not shown), also include a plurality of weight reduction apertures—apertures **241** in fourth bend region and apertures **242** in third bend region. Although the apertures are shown to be significantly in the bend regions, the apertures are not limited and can be large enough such that they also encompass part of portion, e.g., fifth portion **218**.

[0028] Load bearing or traverse portions **202** (although only one is depicted in FIG. **2**(*c*), the other, not shown, load bearing or traverse portion **202**, includes similar apertures in comparable locations) include a plurality of apertures. Load bearing or traverse portions **202** include a plurality of apertures **252** for securing an ancillary rail module **102** (FIG. **1**). Load bearing or traverse portions **202** include a plurality of apertures **256** for securing accessory collateral clamps **107** (FIG. **1**). Load bearing or traverse portions **202** includes a plurality of weight reduction apertures **246** which are used to remove some of the weight of the forward module **101** without impacting the effectiveness of forward module **101**. The back portion of the forward module **101** is designed to couple with mounting module **103**. As such, load bearing or traverse portions **202** include a plurality of apertures **262** for securing forward module **101** to mounting module **103**. The apertures **262** correspond to apertures in mounting module **103**.

[0029] The size and orientation of the weight reduction apertures, e.g., apertures **240**, **241**, **246**, etc, are subject to the designer's wishes balanced with the impact on the efficacy of the weapon system including the impact on accessory interface system **100**.

[0030] FIG. **2**(*d*) depicts a portion of the accessory interface system **100** in a perspective view showing more of the bottom of interface portion **204**. As depicted in FIG. **2**(*d*), third portion **214**, fourth portion **216** and fifth portion **218** include a plurality of apertures to couple a rail system **106** to the respective portion. Third portion **214** includes a plurality of, e.g., four (4) apertures **232**, fourth portion **216** includes a plurality of, e.g., four (4) apertures **232**, and fifth portion **218** includes a plurality of, e.g., four (4) apertures **230**, for respectively being coupled to a rail system **106**. Although described with reference to using rail system **106**, the invention is not limited and can use any appropriate rail system.

[0031] As noted above, portion **218**, portion **216**, and portion **214** include a plurality of weight reduction apertures which are used to remove some of the weight of the forward module **101** without impacting the effectiveness of forward module **101**. Fourth bend region **226** and third bend region **224**, and similarly second bend region **222** (also include a plurality of collinear weight reduction apertures—apertures **241** in fourth bend region **226**, apertures **242** in third bend region **224**, and apertures **243** in the second bend region **222**. Although the apertures are shown to be significantly in the bend regions, the apertures are not limited and can be large enough such that they also encompass part of portion, e.g., fifth portion **218**.

[0032] FIGS. **3**(*a*)-**3**(*d*) depict the ancillary rail module **102** in greater detail. FIG. **3**(*a*) depicts a top view of an initial stage of formation of an ancillary rail module **102** of FIG. **1**. In an exemplary embodiment, ancillary rail module **102** is formed from a substantially rectangularly shaped, substantially flat metal blank **300**, where the metal is quarter inch (0.25") metal being approximately four inches (4") in height and six and one quarter inches (6¼") in width.

[0033] The metal blank **300** is subdivided into further substantially rectangular portions: first portion **310**, second portion **312**, third portion **314**, fourth portion **316** and fifth portion **318** as depicted in FIG. **3**(*a*). First portion **310** and fifth portion **318** are approximately one inch (1") in width, second portion **312** and fourth portion **316** are approximately one half inch (½") in width and third portion **314** is approximately three and one half inches (3½") in width. The metal blank **300** also includes bend regions: first bend region **320**, second bend region **322**, third bend region **324**, and fourth bend region **326**. The bend regions represent where the metal blank **300** is bent during formation to form the desired shape of the ancillary rail module **102**.

[0034] Metal blank **300** is bent along first bend region **320** to form a forty five (45) degree between a plane formed by the face of first portion **310** and a plane formed by the face of second portion **312**. Metal blank **300** is further bent along second bend region **322** to form a forty five (45) degree between a plane formed by the face of second portion **312** and a plane formed by the face of third portion **314**. Metal blank **300** is further bent along third bend region **324** to form a forty

five (45) degree between a plane formed by the face of third portion **314** and a plane formed by the face of fourth portion **316**. Metal blank **300** is further bent along fourth bend region **326** to form a forty five (45) degree between a plane formed by the face of fourth portion **316** and a plane formed by the face of fifth portion **318**.

[0035] FIG. **3**(*b*) depicts a front perspective view of an intermediate stage of forming an ancillary rail module **102**. FIG. **3**(*b*) shows the ancillary rail module after being bent. As a result of the bending, first portion **310** is at a 45 degree angle with respect to second portion **312**. Second portion **312** is at a 45 degree angle with respect to third portion **314**. Third portion **314** is at a 45 degree angle with respect to fourth portion **316**. Fourth portion **316** is at a 45 degree angle with respect to fifth portion **318**.

[0036] FIG. **3**(*c*) depicts a top perspective view of a later stage of forming an ancillary rail module **102**. As depicted in FIG. **3**(*c*), a plurality of apertures is applied to mounting surface **104** (FIG. **1**) to permit mounting of a rail system **105** (FIG. **1**) on ancillary rail module **102**. Thus, third portion **314** includes a plurality of apertures, e.g., **330**, to couple a rail system **105** (FIG. **1**) to the portion **314**. The size, number, and orientation of apertures depend on the rail system to be coupled to so that the apertures in the mounting surface correspond to apertures in the rail system so that the rail system **105** can be coupled to the ancillary module **102**. Although described with reference to using rail system **105**, the invention is not limited and can use any appropriate rail system.

[0037] Ancillary rail module **102** includes a plurality of weight reduction apertures **340**, **342** which are used to remove some of the weight of the ancillary rail module **102** without impacting the effectiveness of forward module **101** and the ancillary rail module **102**. Apertures **340** are primarily located in portion **314**; apertures **342** are primarily located in regions **312**, **316**, and apertures are also located in portions **310**, **318** (not shown). Although the apertures are shown to be significantly in the bend regions, the apertures are not limited and can be large enough such that they also encompass part of a bend portion, e.g., fifth portion **322**.

[0038] FIG. **3**(*d*) depicts a perspective view of a later stage of forming the ancillary rail module **102**. FIG. **3**(*d*) depicts the third portion **314**, fourth portion **316**, and fifth portion **318**. In third portion **314** can be seen apertures **330** for mounting a rail system **105**, and weight reduction apertures **340**. Weight reduction apertures **342** can be seen in fourth portion **316** and weight reduction apertures **344** can be seen in fifth portion **318**. Fifth portion **318** also includes apertures **352** for mounting the ancillary rail module **102** onto the forward module **101**. The size, number and orientation of apertures **352** depend on the size, number, and orientation of the corresponding apertures **252** (FIG. **2**(*c*)) to mount and couple the ancillary rail module **102** to the forward module **101**.

[0039] FIGS. **4**(*a*)-(*d*) depict the mounting module **103** (FIG. **1**) in greater detail. FIG. **4**(*a*) depicts a side view of a portion of the mounting module, more specifically, one of the two support structures **571**. Although only one support structure **571** is depicted and described in FIGS. **4**(*a*)-**4**(*c*), there is a corresponding second structure being a mirror image of that described (as can be seen in FIG. **4**(*f*)) with respect to support structure **571**.

[0040] Support structure **571** includes a structural element section **570** and a coupling bracket section **575**. In an exemplary approach, structural element section **570** has a substantially rectangular main body with a lobe **579** being below and dog-leg-right of the main body. Coupling bracket section **575** is substantially rectangular and having a height comparable to the height of the main body of the structural element section **570**. Coupling bracket section **575** is placed such that a portion of coupling bracket section **575** has a side mating portion which is laterally offset from the main body of structural element section **570**, and in this embodiment is machined as a single component. Coupling bracket section **575** has three (3) apertures **580**. Apertures **580** are used to couple the mounting module **103** to the forward module **101** using corresponding apertures **262** (FIG. **2**(*c*)). One embodiment includes notches **574** in the top, rear of support structure **571** which enables operation of certain weapons or equipment items having somewhat large controls on the sides of the weapon or equipment item without interfering with the operation of the weapon or equipment item.

[0041] FIG. **4**(*b*) depicts a back view of a support structure **571**. As seen in FIG. **4**(*b*), support structure **571** includes a structural element section **570** and a coupling bracket section **575**. Structural element section **570** includes a bend region **572** where the lobe **579** is bent with respect to an upper section of the structural element section **570**. As a result of the bending, the bottom **573** of the lobe **579** allows for coupling of lobe **579** to support structure **571** in the interior of the mounting module **103** (see, for example, FIG. **4**(*f*)).

[0042] FIG. **4**(*c*) depicts a top view of a support structure **571**. As seen in FIG. **4**(*c*), support structure **571** includes a structural element section **570** and a coupling bracket section **575**. Coupling bracket section **575** is on the exterior side of structural element section **570**. As a result of the bending, the bottom **573** results in the interior side of structural element section **570**.

[0043] FIG. **4**(*d*) depicts a front view of a backplate **550**, which includes two apertures **114** and a two lobes **554** extending slightly upward from the main body of the back plate **550**. Apertures **114** are used to couple the backplate **550** to a weapon mount.

[0044] FIG. **4**(*e*) depicts a side view of a backplate **550** being coupled to a support structure **571**. The coupling bracket section **575**, having apertures **580**, is coupled to structural element section **570**. Structural element section **570** is coupled to backplate **550** along section **578**. Although only one support structure **571** is shown, this support structure **571** is representative of the other support structure.

[0045] FIG. **4**(*f*) depicts a front view of a mounting module **103**. As seen in FIG. **4**(*f*) mounting module **103** includes backplate **550** and support structures **571**. As noted above, each support structure **571** includes a structural element section **570** and a coupling bracket section **575** integrated into the exterior side of structural element section **570**. Each support structure **571** also has a lower lobe **579** (FIGS. **4**(*a*)-(*b*)) that is bent so that the lobe extends into the interior of mounting bracket **103**. Backplate **550** includes aperture **114**.

[0046] FIGS. **5**(*a*) and **5**(*b*) and FIGS. **6**(*a*) and **6**(*b*) depict rail systems that can be employed on the accessory interface system **100**. A rail system can be, for example, a picatinny or MIL-STD-1913 rail. FIG. **5**(*a*) depicts a top view of mounting rail **106**. Mounting rail **106** includes a top surface **503** and grooves **502** in the top surface **503**. Mounting rail **106** also includes a plurality of apertures **505** used to couple the mounting rail **106** to another structure. FIG. **5**(*b*) depicts a side view of mounting rail **106**. As seen in FIG. **5**(*b*), mounting rail **106** includes a top surface **503** and grooves **502** in the top surface **503**. The mounting rail also includes a side **507**.

The spacing, size, depth and arrangement of the apertures, top surface, sides, and grooves are dependent on the application and desired characteristics of the designer. The size and spacing of the apertures should correspond with the desired mounting apertures on the forward module **101** or the ancillary rail module **102**. Although depicted as mounting rail **106** being different from mounting rail **105**, the invention is not so limited. For example, mounting rail **106** can be the same as mounting rail **105**. Alternatively, mounting rail **106** can be similar to mounting rail **105**, e.g., where both have similar design features with the significant exception that one mounting rail is longer than the other mounting rail. Furthermore, although the invention depicts using a rail system as a method for coupling an accessory (ies) to an accessory interface system, the invention is not so limited.

[0047] FIG. **6**(*a*) depicts a top view of mounting rail **105**. Mounting rail **105** includes a top surface **513** and grooves **512** in the top surface **513**. Mounting rail **105** also includes a plurality of apertures **515** used to couple the mounting rail **105** to another structure. FIG. **6**(*b*) depicts a side view of mounting rail **105**. As seen in FIG. **6**(*b*), mounting rail **105** includes a top surface **513** and grooves **512** in the top surface **513**. The mounting rail **105** also includes a side **517**. The spacing, size, depth and arrangement of the apertures, top surface, sides, and grooves are dependent on the application and desired characteristics of the designer.

[0048] FIG. **7** depicts the assembly of components parts of the accessory interface system **100**. As seen in FIG. **7**, five rails **106** have been coupled to the forward module **101**. Apertures **505** (FIG. **5**(*a*)) in a rail **106** have been lined up with corresponding apertures **230** (FIG. **2**(*c*)). A fastener **623** couple a rail **106** to the forward module **101**. Collateral clamps **107** have been coupled to forward module **101** using fasteners **619** which pass through an aperture (not shown) in collateral clamp **107** and into a corresponding aperture **256** (FIG. **2**(*c*)) in forward module **101**. Although only one side of forward module **101** is depicted, the features depicted in this side are representative of features also present in the other side.

[0049] As seen in FIG. **7**, rail **105** has been coupled to ancillary rail module **102**. Apertures **515** (FIG. **6**(*a*)) in a rail **105** have been lined up with corresponding apertures **330** (FIG. **3**(*c*)). Fasteners **621** couple a rail **105** to ancillary rail module **102**. Ancillary rail module **102** is coupled to forward module **101**. Apertures **352** (FIG. **3**(*d*)) in ancillary rail module **102** have been lined up with corresponding apertures **252** (FIG. **2**(*c*)). Fasteners **611** couple ancillary rail module **102** to the forward module **101**.

[0050] In an exemplary embodiment, the forward module **101** provides several locations to mount ancillary rail module **102**. Although weapon sights are often placed to the rear of a weapon, some weapon users may opt to mount a sight further away for increased eye relief. Some weapon users may also choose to use two sights, each zeroed for a different distance. Thus, an easily movable ancillary rail module **102** provides flexibility in placement of a sight or other accessory for use with a weapon.

[0051] Mounting module **103** is coupled to forward module **101**. Apertures **580** in mounting module **103** have been lined up with corresponding apertures **262** (FIG. **2**(*c*)). Shear fasteners **613** couple mounting module **103** to the forward module **101**. The accessory interface system **100** offers at least one designed failure point so as to prevent damage to the weapon mount or a weapon mounted on the weapon mount. If the accessory interface system **100** becomes overloaded or exposed to too much stress or force, the shear fasteners **613** will shear and cause the accessory interface system, or at least a portion of the accessory interface system **100**, to effectively break-away, leaving the weapon functional and the weapon mount unaffected. The designed failure point, breakaway section **109**, permits forward module **101** to break away from mounting module **103**. The designer determines what is required to trigger the forward module **101**, due to, e.g., excess shear force or load on the forward module **101**, to break away. In an embodiment, the selection and arrangement of the method of fastening forward module **101** to mounting module **103** mostly dictates the breakaway parameters. For example, the selection and employment of six, quarter inch (¼") diameter stainless steel fasteners (e.g., screws) for use as shear fasteners **613** provides a calculable amount of force necessary to shear the shear fasteners **613** and decouple forward module **101** from mounting module **103**. Ideally, the force required to break away is less than a force that would damage, impact, or impair the weapon in the weapon mount and or weapon mount connected to the accessory interface system. Although stainless steel fasteners are disclosed for use as shear fasteners **613**, the invention is not necessarily limited, and any appropriate fastening system can be employed. In a various aspect, not disclosed in the Figure, a fastening system coupled to the forward module **101** is employed which permits quicker/easier retrieval of the forward module **101** in the event that the forward module **101** breaks off from the mounting module **103**. The retrieval system is, for example, a lanyard or retaining wire, coupled to at least one point on the forward module **101** and at least one point on the mounting module **103**.

[0052] The fastening system **115** employs the bolts **112** to fasten the mounting module **103** to the weapon mount (not shown), where the bolts **112** may be the bolts previously existing in the weapon mount. Alternatively, bolts **112** are similar to the bolts previously existing in the weapon mount but are slightly longer to account for the mounting of the accessory interface system **100**. Using the mounting system previously existing in the weapon mount enables retaining the buffer system of the weapon mount.

[0053] In another aspect, a second designed failure point is included to permit ancillary rail module **102** to break from the forward module **101** in the event that a large stress or shear force(s) is applied to the ancillary rail module **102**. In the event, for example, that the forward module **101** broke off from the mounting module **103**, the ancillary rail module **102**, (being coupled to the forward module **101**) would be resting on a barrel of a weapon in the interior space of the accessory interface system **100**; whereby the ancillary rail module **102** would be supporting the forward module **101** and anything coupled to the forward module **101**. Therefore, it could be desirable to have a second engineered failure point in the system that couples the ancillary rail module **102** to the forward module **101**. Accordingly, the ancillary rail module **102** would break off from the forward module **101** and reduce the chance that ancillary rail module **102** will damage and/or effect the operation of the weapon. Alternatively, a retrieval system is employed to couple the ancillary rail module **102** to the forward module **101** or the mounting module **103**, to permit quick retrieval of the ancillary rail module **102**. An example fastening system could include a flexible lanyard (not shown) which couples the ancillary rail module **102** to the forward module **101**. The flexible lanyard could also have

quick release pins which couple one or both ends of the lanyard to a particular component (e.g., **101**, **102**). Consequently, retention and implementation of the desired second engineered failure point is considered in the selection and implementation of appropriate fastening mechanisms, e.g., screws or bolts **611**. Examples of such fastening mechanisms include shear fasteners or bolts which have a desired shear strength which is more than the force associated with typical use and forces arising from accessories which are coupled to various components such as the forward module **101**, ancillary rail module **102**, and/or mounting module **103**.

[0054] FIG. **8**(*a*)-(*c*) depict the accessory interface system **100** in application with a weapon and weapon mount. FIG. **8**(*a*) depicts a side perspective view of accessory interface system **100** surrounding a weapon **868** which is mounted on a weapon mount **160**. The accessory interface system **100** also provides flexibility in use. For example, the accessory interface system **100** includes five mounting surfaces **210**, **212**, **214**, **216**, **218** (e.g., FIGS. **2**(*a*)-(*d*)), plus the mounting surface of the ancillary rail module **102**, where each mounting surface is aligned with a common centerline or central axis. This centerline coincides directly with the radial axis of a bore or barrel of the weapon **808**. In an approach, each mounting surface is equidistant from the common centerline. In the case of a laser, once the device is zeroed at one location of a mounting surface, it can be mounted on any of the other mounting surfaces and retain zero. The same laser bore sight chart can also be used to zero the laser regardless of which mounting surface the laser uses; thus, different bore sight chart are not necessarily required for each mounting surface. Similarly, an optical sight can be placed on one mounting surface and zeroed. The optical sight can be moved and mounted on another mounting surface and the optical sight will not require adjustment to be zeroed. In a preferred approach, similar rails are mounted on each of the mounting surfaces, such that the rail will not affect the alignment of devices mounted on the rail. Thus, for example, an optical sight can be mounted on a rail system that is, in turn, mounted on one mounting surface and zeroed. The optical sight can be moved and mounted on a rail system that is, in turn, mounted on another mounting surface and the optical sight will not require adjustment to be zeroed.

[0055] As noted above and depicted in FIG. **8**(*a*), the accessory interface system **100** provides for cable management. Lights and lasers can be controlled remotely at the rear of the weapon via cables. These cables are held along the rail via collateral clamps **107**, preventing the pinching or melting of cables. This minimizes having cables that are free to hang loose or the need to secure cables using zip-ties. With an open design, the collateral clamps **107** allow for the quick attachment and removal of cables, unlike zip-ties which are more permanent in nature and must typically be cut off, possibly resulting in the inadvertent cutting of a cable. For example, a collateral clamp **107** is formed from ½ inch (½") wide by three inch (3") strip of nylon, having a loop of approximately one and one quarter inch (1¼") diameter on one end and the other end of the nylon strip is coupled to the forward module **101**. The loop can be pulled open, cable placed in the interior space, and the loop released, thereby reforming the loop with the cable inside. Although the cable clamp is described with respect to be fashioned from nylon and in the shape of a loop, the invention is not so limited.

[0056] FIG. **8**(*b*) depicts a forward-looking, side perspective view of accessory interface system **100** surrounding a weapon **868** which is mounted on a weapon mount **160**. As depicted in the figure, the barrel of the weapon **808** is located within the interior space of the forward module **101**. The barrel of the weapon **808** is also located within the interior space of the ancillary rail module **102** which has a rail **105** fastened on top of the ancillary rail module **102**. Also depicted is a portion of mounting module **103** coupled to forward module **101**.

[0057] FIG. **8**(*c*) depicts a forward-looking, side perspective view of accessory interface system **100** surrounding a weapon **868** which is mounted on a weapon mount **160**. As depicted in the figure, the barrel of the weapon **808** is located within the interior space of the forward module **101** which has five (5) rails **106** fastened on it. The barrel of the weapon **808** is also located within the interior space of the ancillary rail module **102**. As noted above and depicted with reference to, for example, FIG. **8**(*a*), an advantage of having the accessory interface system **100** coupled to sections of a weapon mount in such a way as to avoid structure directly underneath the weapon is that this approach does not significantly impact or limit the depression of the equipment item or weapon nor does it significantly impact or limit the range of motion of the weapon having the accessory interface system **100**. This difficulty with range of motion was discovered after attempts were made to create a mount with mounting structure underneath a weapon, e.g., under a barrel of the weapon **808** section. Other advantages exist including avoiding certain types of stress loading on a structure which passed underneath a portion of the barrel of a weapon **808** in closer proximity to a weapon mount **160**.

[0058] FIG. **9** depicts an accessory interface system in application with a weapon and weapon mount and a ballistic shield. FIG. **9** depicts a side perspective view of accessory interface system **100** surrounding a weapon **868** which is mounted on a weapon mount **160**. As depicted in the figure, the barrel of the weapon **808** is located within the interior space of the forward module **101**. The barrel of the weapon **808** is also located within the interior space of the ancillary rail module **102** which has a rail **105** fastened on top of the ancillary rail module **102**. A ballistic shield **888** is shown coupled to mount assembly **160** (e.g., see FIG. **1**). In another approach, ballistic shield **888** may be coupled in whole or part to the rail **105** (or **106**) where it is not undesirable for the ballistic shield to also detach when an engineering failure point which couple the rail **105** to the mount assembly **160**, e.g., **613**, shear away. The ballistic shield preferably is made from a material which provides protection from projectiles or shrapnel and can also be designed to provide cover and concealment from a hostile party e.g., a sniper. The ballistic shield may also have structures which provide only concealment such as a fabric cover which extends beyond one or more edges of a hardened area of the shield which can also be designed to be fire retardant. Although the accessory interface system **100** is shown with an exemplary ballistic shield **888**, any reasonably shaped and sized ballistic shield **888** can be employed, as well as multiple same or different ballistic shields can be employed contemporaneously or individually.

[0059] Efforts to design accessory mounting systems have run into a wide variety of problems or operating mode limiting design choices. The various problems associated with current art accessory mounting designs are increasing rather than decreasing given an increased desire to have a wider variety of accessories in use under an increasing variety of operating conditions. In the development of the above refer-

enced invention, finite element modeling and analyses were performed for an accessory interface system **100** which maximized the number and variety of accessories, increased the number of ballistic or other type of shield/shrouds which could be used, addressed a variety of shortcomings associated with existing designs (e.g., weight, power management, range of motion, traversal, or elevation associated with equipment/weapon utilization), and reduced risks associated with a number of operating conditions/events. Testing was also accomplished to ensure various embodiments of an equipment/weapon and accessory mounting system was compatible for use with a weapon mount **160** in order to determine the structural integrity of an accessory interface system **100** under shock loading. This analysis was also conducted due to the need to ascertain the reliability of the accessory interface system **100** given it was found that initial selections of various combinations of components did not yield predictable results other than equipment failure or rejections of existing or experimental designs by various user classes. Thus, extensive testing was required in order to ascertain which designs would function as intended under the conditions that the various systems were to be employed. During these analysis efforts, experiments were conducted including ones on weld size and geometry as well as shear fastener sizes and specifications. In the course of the testing, including testing described herein, various design changes had to be made given testing results showed design failure in various component choices and design features for the combination of features, capabilities, and structures associated with various embodiments of the invention in this case. These analyses included finite element analysis modeling a heavy accessory mounted to an exemplary accessory interface system **100** where the accessory was a 10 lb spotlight (not shown).

[0060] One analyses consisted of a series of static and dynamic analyses. One static analysis was performed to determine preferred weld sizes and geometry and to also determine various worst case loading scenarios. Once design changes were made, revised models were subjected to a more severe dynamic shock loading analysis as outlined in MIL-STD-810. Separate models were constructed for the side, angle, and bottom mounted accessory configurations.

[0061] Various accessory interface system **100** parts were constructed of a fine mesh of three dimensional solid elements. Selected accessory interface system **100** parts were assigned material properties 4340 steel in accordance with AMS 6414. The weapon mount front cross member **161** was given material properties of 17-4PH H900 stainless steel. Pertinent material properties are listed in Table 1. The shear fasteners **613** and bolt **112** were modeled using rigid beam elements. The weapon mount cross member (e.g., 161) was rigidly constrained on its left and right surfaces. Contact interactions were defined between bolted or fastened connection contacting surfaces. An exemplary accessory, e.g., a spotlight mass, was coupled to the appropriate mounting hole surfaces. In one test, it was located four inches from the mounting surface in the middle of the bolt hole pattern. Static 20 g inertial loads were applied to each model in the up, down, lateral, fore, and aft directions. A 20 g static load is one worst case load used to analyze helicopter structures for a potential aviation user.

TABLE 1

Material Properties

Property	AISI 4340	17-4PH H900
Density (lb_f-s_2/in_4)	0.000732	0.000735
Young's Modulus (psi)	29,000,000	28,500,000
Poisson's Ratio	0.32	0.27
Tensile Yield Strength (psi)	217,000	170,000
Ultimate Shear Strength (psi)	156,000	123,000
Ultimate Tensile Strength (psi)	270,000	190,000

[0062] Static modeling results for a number of embodiments showed worst case loads were in a down direction for the side and angle mount configurations. Additional tests showed a number of embodiments have a worst case load in a lateral direction for a bottom mount configuration

[0063] Weld configuration and size for a number of embodiments were determined to be a 0.125 full penetration groove finished on both long sides of the weld joint with 0.06 fillet welds. Table 2 lists worst case stresses/safety margins for each component of certain embodiments for each load. All safety margins are based on ultimate stresses. Safety margins for exemplary bolts **112** were based ½-13 UNC 300 series stainless steel (i.e. ultimate tensile strength=80 ksi, ultimate shear strength=50 ksi). Exemplary safety margins for exemplary shear fasteners are based on #8-36UNF SAE grade 8 fasteners (i.e. ultimate tensile strength=150 ksi, ultimate shear strength=120 ksi). Static analysis for various redesigned embodiments found that the new combinations and components passed the worst case 20 g static loading testing.

TABLE 2

Static Analysis Summary

	Side Mount 20 g's Down		Angle Mount 20 g's Down		Bottom Mount 20 g's Lateral	
Exemplary Component	Max Stress	MS	Max Stress	MS	Max Stress	MS
Rail 106	76970	2.50	69980	1.85	188900	0.43
Backplate 550	219900	0.22	218800	0.23	217500	0.24
Weapon mount Cross Member 161	175600	0.08	161700	0.17	142700	0.33
Bolts 112	N/A	1.29	N/A	1.38	N/A	2.81
Shear fasteners 613	N/A	0.00	N/A	0.03	N/A	0.04

[0064] Other tests were also completed to include a dynamic model test. The dynamic model set-up is similar to the static model set-up described above with the significant exception that the mesh is coarser and continuum shell elements were used instead of three dimensional solids. A rigid body, which was constrained in all directions, was placed inside the accessory interface system **100** to simulate movement of a heavy equipment item, such as a barrel of the weapon **808**. The dynamic loads were applied as 40 g acceleration for a 23 ms duration and 75 g acceleration for a 13 ms duration sawtooth shock pulses in accordance with MIL-STD-810 Method 516.5 page 516.5-14.

[0065] Results of dynamic modeling for a number of embodiments focused on a side mount configuration loaded

with a 75 g acceleration with a 13 ms duration shock pulse in the down direction which is worst case and most likely direction to be severely loaded in one or more field utilization scenario (e.g., river patrol boat, mobile firefighting, submersible, whaling, ship mounted, dismounted infantry, or other special operations). An exemplary bolt **112** under test fails at a time of 0.110 s. However, selected shear fasteners, e.g., 613, fail before that time (the right and left top shear fastener **613** at t=0.015 s, the left aft shear fastener **613** at 0.02 s, the right bottom shear fastener **613** at 0.035 s, and the right aft and left bottom shear fastener **613** at 0.065 s). Stress plots reveal that stress for the left section (viewed from the muzzle end of a weapon) of backplate **550** exceeds ultimate material strength (i.e. 260 ksi) at 0.0175 s. At t=0.035 s the exemplary weapon mount cross member **161** exceeds its ultimate stress of 190 ksi but the stress is localized.

[0066] Results from different analyses conducted on various embodiments found that redesigned accessory interface system **100** passed static 20 g loading. As discussed in Table 2, shear fasteners **613** likely have the lowest safety margin which was one goal of various embodiments design. Dynamic analyses revealed that two exemplary shear fasteners **613** would likely break before stresses throughout the rail, e.g., 100, exceed ultimate stress levels associated with one set of potential field conditions. One of the exemplary analysis models does not allow all of the shear fasteners **613** to "release" and thereby load the remaining shear fasteners, e.g., **613** at one potential point of failure. One means for determining if a shear fasteners **613** will shear sooner than expected is to insert failure criteria for the shear fasteners **613** or re-run an analysis from a point of failure without the shear fasteners **613** or additional actual shock testing. It may be desirable to increase the size of the fillet welds (e.g., welds coupling sections **570**, **550** of mounting module **103**) to an exemplary 0.090 inch at least on outer welds. The shear fasteners **613** can remain #8-36UNF SAE grade 8 screws or equivalent (i.e. minimum ultimate tensile strength=150 ksi, minimum ultimate shear strength=120 ksi).

[0067] In one exemplary embodiment, an accessory interface system **100** is modular. For example, a same type weapon is employed in different contexts, where the context dictates certain design features, e.g., length of the accessory interface system **100**. An embodiment can be constructed by removing two mounting bolts e.g., 112, that fasten the accessory interface system **100** to a weapon mount **160**, the accessory interface system **100** can be removed and a different accessory interface system **100** easily mounted in its place. Additionally, different devices or weapons are mountable on a same type of weapon mount **160**. As such, it may be desirable to have different design features corresponding to a different device, respectively. As noted above, straightforward design modification can incorporate an exchange of one accessory interface system **100** for another accessory interface system **100**, accessories and the ability to include accessories can be tailored to different devices on the weapon mount.

[0068] Although the invention may depict one method of fastening an element to another element, the invention is not so limited. Different methods of fastening can be employed as appropriate under the circumstances or as desired by the user or designer in view of a wide variety of design considerations and required testing to verify utility and safety of a particular design.

[0069] While the invention has been described and illustrated with reference to specific exemplary embodiments, it should be understood that many modifications and substitutions can be made without departing from the spirit and scope of the invention. For example, the invention describes using a rail system **106** on the forward module **101** and second rail system **105** on the ancillary accessory module **102**, the invention is not so limited and any combination of rail systems can be used, preferable such that heights are substantially all the same (to maintain equidistance from common centerline of weapon) and use similar mechanisms to fasten the rail system to the accessory interface system **100**. Accordingly, the invention is not to be considered as limited by the foregoing description but is only limited by the scope of the claims.

1.-**13**. (canceled)

14. An accessory interface system for coupling accessories to a mount, comprising:

a forward module having a first mounting surface,

an ancillary rail module adapted to be removably coupled to said forward module, said ancillary rail module having a second mounting surface, said first mounting surface being substantially aligned with a common center line in an interior of the forward module, said second mounting surface being substantially aligned with said common center.

15. The accessory interface system of claim **14**, further comprising:

said ancillary module being removably coupled to a first location on said forward module.

16. The accessory interface system of claim **14**, further comprising:

said ancillary module being removably coupled to a second location on said forward module.

17. The accessory interface system of claim **14**, further comprising:

a first rail system coupled to said mounting surface of said forward module.

18. The accessory interface system of claim **17**, further comprising:

a second rail system coupled to said second mounting surface of said ancillary rail module, where a side of said second rail system distal from said second mounting surface and a distance from a side of said first rail system distal from said first mounting surface is substantially equidistant with respect to said common center line in said interior radial axis of the second module.

19. The accessory interface system of claim **15**, further comprising:

a removable fastening system for removably coupling said ancillary rail system to said forward module.

20. An equipment interface system, comprising:

an equipment mount;

a first interface section comprising a first interface and second interface portion, said first interface portion is adapted to mechanically couple to said equipment mount; and

a second interface section comprising a third interface portion adapted to couple to said second interface portion, wherein said second and third interface portions are adapted to maintain structural integrity and relative position to each other up to a first predetermined force, wherein said first interface portion is adapted to maintain structural integrity and relative position with said equipment mount up to a second force, wherein said first force is less than said second force, wherein said second and third interface portions are adapted to mechanically

decouple from each other after a force greater than said first force is applied to at least said second interface section.

21. The equipment interface system of claim **20**, further comprising:

a third interface section comprising a fourth interface portion,

wherein said second interface section further comprises a fifth interface portion adapted to couple to said fourth interface portion, wherein said fourth and fifth interface portions are adapted to maintain structural integrity and relative position to each other up to a third predetermined force, wherein said fourth and fifth interface portions are adapted to mechanically decouple from each other after a force greater than said third force is applied to at least said third interface section.

22. The equipment interface system of claim **21**, further comprising:

a retrieval coupling system adapted to couple said first interface section to said second interface section, said retrieval coupling system adapted not to interfere with decoupling said second interface portion from said third interface portion, said retrieval coupling system adapted to maintain a secondary mechanical coupling between said first interface section to said second interface section.

23. The equipment interface system of claim **22**, further comprising:

a second retrieval coupling system adapted to couple said third interface section to said second interface section, said second retrieval coupling system adapted not to interfere with decoupling said second interface portion from said third interface portion, said retrieval coupling system adapted to maintain a secondary mechanical coupling between said first interface section to said third interface section.

24.-**34**. (canceled)

35. A weapon system including an accessory interface system for coupling an accessory to a mount, comprising:

an equipment mount adapted to be coupled to a weapon, said equipment mount adapted to traverse, elevate, traversal elevate, traversal depress, and diagonal movements;

an accessory interface system adapted to be coupled to said equipment mount, said accessory interface adapted to surround at least a portion of a barrel of said weapon, said accessory interface system adapted to not significantly affect the movements of said equipment mount, said accessory interface including a shearing portion adapted to decouple a first portion of said accessory interface system from a second portion of said accessory interface system after when a shearing force is received at said shearing portion.

36. The weapon system of claim **35**, wherein said accessory interface system further comprises an open region below a bottom side of said barrel of said weapon.

37. The weapon system of claim **36**, wherein said accessory interface system further comprises a second open region, said equipment mount adapted to be coupled to a equipment mount stand, said second open region being in an area, of said accessory interface system substantially in an area where the equipment mount stand and the accessory interface system are in closest proximity when the mount is traversed in a substantially vertical depression mode.

38. The weapon system of claim **35**, wherein said shearing force is at least 175 kilograms per square inch.

39. A method of making an accessory interface system, comprising the steps of:

forming a forward module having a plurality of mounting surfaces;

forming each of said plurality of mounting surface being substantially aligned to a common center line in an interior of the forward module

forming a mounting module; and

coupling said mounting module to said forward module, said mounting module adapted to be coupled to a weapon mount.

40. The method of claim **39**, further comprising the steps of:

forming an ancillary module; and

removably coupling said ancillary module to said forward module.

41. The method of claim **39**, wherein said step of coupling further comprises forming a coupling system, such that coupling system maintains its coupling when subject to a force up to at least a first force level and when subject to a force that exceeds a second force level, the coupling system un-couples.

42. The method of claim **39**, wherein said first force level is a 20 G load.

43. The method of claim **39**, wherein said second force level is 120 kilograms per square inch.

44. The method of claim **39**, wherein said second force level is 175 kilograms per square inch.

* * * * *